


Material Safety Data Sheet

Dr. Jean Bausch KG
Oskar-Schindler-Str. 4
50769 Cologne - Germany
Phone: ++49-221-70936-0
Fax: ++49-221-70936-66
Internet: www.bauschdental.de
eMail: info@bauschdental.de

US-Sales Office:
Bausch Articulating Papers Inc.
12 Murphy Drive, Unit 4
Nashua, NH 03062 - U.S.A
Phone & Fax: (603) 883-2155
Internet: www.bauschdental.com
eMail: info@bauschdental.com



Identity (As Used on Label and List)

Trade Name: Bausch Articulating Paper 40 μ extra thin red

Code: BK 10 (booklets of 200 strips), BK 12 (sheets), BK 14 (rolls 16 mm), BK 16 (rolls 22 mm)

Chemical Castor Oil (Pharmaceutical Quality), cellulose (Paper oxigene bleached), C.I. Pigment red 49,

Description: Tech Binder (mixed polymerization of artificial substance)

Product Use: Dental Material, for Marking of Occlusal Surface

Section I

Manufacturer's Name	Emergency Telephone Number
Dr. Jean Bausch KG	++49-221-70936-0, (603) 883-2155
Address (Number, Street, City, State, and Zip Code)	Telephone Number for Information
Oskar-Schindler-Str. 4	++49-221-70936-0, (603) 883-2155
50769 Cologne-Germany	Date Prepared
Bausch Articulating Papers Inc.	11.02.1999
12 Murphy Drive, Unit 4	Signature of Preparer (optional)
Nashua NH, 03062 -U.S.A	Peter Bausch

Section II - Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
none				

Section III - Physical / Chemical Characteristics

Boiling Point	Specific Gravity (H ₂ O = 1)	Melting Point
n.a.	0.91 (D)	
Vapor Pressure (mm Hg.)	Vapor Density (AIR=1)	Evaporation Rate (Butyl Acetate = 1)
n.a.	n.a.	n
Solubility in Water	Appearance and Odor	
none	red strips, sheets, and rolls of paper	

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
> 300°C (572°F) (Literature)		n.a.	n.a.

Extinguishing Media

Use dry chemicals or carbon dioxide; water may be ineffective, but should be used to keep fire exposed containers cool.

Special Fire Fighting Procedures

not required

Unusual Fire and Explosion Hazards

Firefighters should wear self-contained breathing apparatus in the positive pressure mode with a full facepiece when there is a possibility of exposure to smoke, fumes, or hazardous decomposition products.