



Standard Features:

- Cast aluminum with steel reinforcement
- Hydraulic base and back
- Synchronized back and seat movement
- Adjustable backrest speed
- Adjustable base down speed
- 2 Programmable pre-positions
- Trendelenburg position

- Automatic return / Last position pre-sets
- Foot control
- 60° horizontal swivel base
- Double articulating headrest
- Trip pan safety shut-off
- 5 Year limited warranty



Standard Features:

- Thin back with lumbar support
- Anatomically correct back pivot point
- Adjustable double articulating headrest with contoured cushion
- Four manual chair movements and 2 programmable positions are standard
- Synchronized back and toe board recline
- Upholstery is designed fore easy and quick clean-up
- · Heavy vinyl scuff guard for toe board
- Sturdy all-metal construction

- All pivot points have permanently lubricated bearings
- Hydraulic lift system
- Quiet and dependable operation
- Chair functions are digitally controlled by a microprocessor
- Automatic return to exit
- Instant override on automatic functions
- Chair is designed for maximum serviceability
- Safety shut-off on base
- Precision photo-electric positioning



· Double articulating headrest

Articulating dual axis headrest re-positions the patient oral cavity to view the upper and lower arches without the need of changing the headrest position.

• Easy Wipe Down Contour Upholstery

Seat upholstery provides extra comfort and high durability.





Seat Rotation Lock

Lever locks seat into desired position.

Foot Control

Hands-free positioning the patient. 2 programmable positions plus an entry/exit position, last position and a manual disc-type positioning control.

• Solid All Metal Construction

Quiet Hydraulic System with Stable Vertical Lift

SPECIFICATIONS

Lifting/lowering mechanism: Hydraulic, cantilever type

Initial height/stroke: 15-1/2" (395mm) / 15" (380mm)

Backrest Reclining: Axis mechanism

Backrest Reclining angle: 0° (horizon) – 70°

Seat tilting: Synchronized with backrest

Seat tilting: 10° —20°

Preset Positions: Microcomputer controlled P1, P2,

LP (last position) and AR (auto-return)

Chair rotation angle: 30° each (left and right)
Headrest: Dual axis type
Safety switch: Under main link

Emergency stop: Any switch can cancel the automatic movement

Packing dimensions:

Chair: 54" x 34" x 31" / 310 lbs.
Cushion: 51" x 9" x 23" / 20 lbs.



